Lot 5,
Keaahala Springs Tract,
Keaahala, Kaneohe,
Koolp. Oahu.

Copy furnished Land Office,

October 31, 1927

File in Carton 44.

C
O
P
Y

Territory of Hawaii

Office of the Government Survey

Honolulu, T. H., October 25, 1927

Lot 5,
Keaahala Springs Tract,
Keaahala, Kaneohe,
Koolaupoko, Oahu.

Being a portion of Lot 8, Grant 6174 to William Henry,
of the Keaahala Homesteads, Kaneohe, Oahu.

Beginning at a 3/4" galvanized iron pipe at the South-east corner of this piece, on the West side of a 20 foot road, the same being the North corner of Lot 6, the coordinates of said point of beginning referred to the Government Survey Triangulation Station "COOLIDGE", being 1352.5 feet South, 1511.9 feet West, and running by true azimuths from the above described initial point:-

1. 73° 20' 545.2 feet along Lot 6 to a pipe;
2. 190° 44' 225.0 feet to a pipe;
3. 253° 15' 112.0 feet to a pipe;
4. 265° 30' 140.0 feet to a pipe;
5. 248° 30' 180.0 feet to a pipe;
6. 237° 52' 88.0 feet to a pipe;
7. Thence curving to the right with a radius of 80 feet, the direct azimuth and distance being, 17° 43' 59.9 feet to a pipe;
8. Thence curving to the left with a radius of 120 feet, the direct azimuth and distance being, 356° 34' 163.9 feet to the point of beginning and containing an area of 94,091 square feet.

Compared:
October 26, 1927
H. E. Newton
Deputy Surveyor

By H. H. Allen (Signed)
Surveyor